

EN AVANT 30

TECHNICAL INFORMATION



120

mt
Bollard Pull
Offshore & Anchorhandling tug

Muller.

EN AVANT 30

AHT DEEPSEA | FiFi2 | SALVAGE & ESCORT

General Information

Year built	November 2011
Builder	Astilleros Armon Vigo, S.A. Pontevedra, Spain
Build type	ASD, FiFi 2, Escort, Deepsea, AHT & Salvage tug
Class	Bureau Veritas
Classification	Unrestricted Navigation. HULL MACH Tug. Escort Tug, Fire fighting ship 2, Oil recovery ship AUT-UMS AUT-PORT SYS-NEQ-1 INWATERSURVEY

Port of registry & Flag	Dordrecht, The Netherlands
IMO	9597317
Callsign	P B P T

Main Particulars

Length o.a.	40.70 m
Breadth mid/o.a.	14.40 / 15.50 m (incl. D-fenders)
Depth	6.90 m
Draught min/max	6.50 / 7.30 m
Gross/Nett tonnage	927 GT / 278 NT
Displacement empty/full	1476 / 2015 T
Lightship weight	1274 T

Performance

Bollard Pull cont. / max.	120 T
Speed	14.3 knots

Propulsion system

Main Engines	2 x MAN 9L 27/38
Total power	9,000 hp (6.750 kW) at 800 rpm
Azimuth Thrusters	2 x SCHOTTEL, type SRP 3030 CPP
Propellers	2 x 3400mm controllable pitch
Bow Thruster	1 x SCHOTTEL 450 kW

Auxiliary Equipment

Auxiliary Engine	2 x MAN D2876 LE301, each 345kW @ 1500 rpm
Emergency/harb. set	1 x MAN D2866 LXE20, 177kW @ 1500 rpm
Shaft Generators	Siemens Electronic 250kW 400V 50Hz
FW maker	4m ³ /day basis Rev. Osmosis system

Deck Lay-out

Free Deck Space	185m ² - well suited for Anchors and Materials.
Deck Crane	1 x PALFINGER PK18500MD, SWL 940kg @ 13,10 m
Towing aft-winch	IBERCISA Hydraulic driven waterfall w. split drum Drum 1 1 x 1000 m IWRC ø64 mm Drum 2a 1 x 400 m IWRC ø64 mm Drum 2b 1 x 400 m IWRC ø64 mm

Capacity aft-winch	Pull 110 T / Break Holding 250 T
Duty on towing	95 T line pull at 0-14m/min, 220 T brake load.
Spare tow wire winch	IBERCISA Hydraulic driven winch, BT Pull, placed underdeck, fitted wire 1 x 1000m IWRC ø64 mm
Towing hook aft	1 x FERRI disc type 1514, SWL 130 T
Towing/Escort hook bow	1 x FERRI disc type 1514, SWL 130 T
Towing/Escort winch bow	2 x ROLLS ROYCE hydraulic driven Anchor/Escort winch type TW4200/1000, each with 1 drum fitted with 300m ø78 mm Dyneema rope

Duty on towing	110 T dynamic Pull, 420 T brake holding load
AHT equipment	1 x Karmoy Karm Fork 2 x Karmoy Towing Pins, rotational with locking plate 2 x Karmoy guiding pins with hardened rollers in aft bulw., SWL 50T 2 x IBERCISA Hydraulic driven tiggerwinch 220/40 10T Pull, 15 T Hold each Stern Roller 250 T SWL, dims. 4000mm x ø1800 mm

Anchorsystem	2 x ROLLS ROYCE Hydraulic driven anchor winches Anchors 1140 kg each 8 + 8 chain lengths
---------------------	---

Salvage & anti-pollution equipment

Salvage equipment

2 x Elec. subm. pumps, 200m³/h cap. each, fitted with hoses and connections, cutting & welding equipment, ropes, wires, shackles, stretchers, pennant wires, towing chains, diving equipment. 2 x weelhouse remote contr. searchlights, fitted with 2000W Xenon lights.

Anti-pollution equipment

2 x Rec-oil tanks total capacity 120m³
1 x Rec-oil pump 20m³/hr
2 x Dispersant booms 6,00m, 2 spray booms with nozzles
1 x Dispersant Pump

Fire fighting equipment

2 x main pumps KVAERNER 3600m³/h cap. each, 2 x elec. remote contr. monitors for water/foam with Fog/ Spray/ Jet fully compliant with FiFi2

Tank capacities

Fuel Oil (MGO) incl. Rec-oil	549.42 m ³
Rec-oil (MGO)	119.66 m ³
Fresh water	43.32 m ³
Lub/Hydr. Oil	63.10 m ³
Sludge	7.00 m ³
Dirty Oil	7.00 m ³
Sewage tank	8.35 m ³
Bilge water	14.49 m ³
Water Ballast	103.04 m ³

Mob

1 x SOLAS Rescue Boat; 1 x Service/Work Boat

Accommodation

Living quarters fully heated & air-conditioned, suitable for a crew of 14
4 single cabins with WC and Shower
5 double cabins with WC and Shower
Crew lounge, deck office, mess-room, galley, walk-in store, one cold store (4°C) and one freezer store room (-20°C)

Nautical & communication

GMDSS area	A3 equipped
Compass	Gyro Compass SIMRAD GC-80 Satellite Compass Furuno SC-50
Radar system	Furuno FAR 2117 X25 Kw Furuno FAR 2137 S30 Kw
GPS	2 x Furuno GP-150
Autopilot	SIMRAD AP-50
Echo sounder	Furuno FE700
Speedlog	Furuno DS-80
VHF Radio Telephone	2 x Furuno FM880
VHF Handheld	3 x GMDSS McMurdo R2
Navtex	Furuno NX-700
AIS	Furuno FA-150
Communication	VSAT - Iridium - SSB - Phones
ECDIS system	2 x Transas Navi-Sailor 4000 system
Weather system	Meteogroup Offshore SPOS onboard
Weather station	Wind system WS200 Furuno RD-33
Inmarsat C System	2 x Inmarsat C FC 15, 1 x Sys. FC250
VSAT system	Data / TV, intellian by Radio-Holland
Maintenance system	MARAD 4.43 system onboard & office

Contact Details

E-mail, VSAT	ea30@muller-dordrecht.nl
E-mail Office	operations@muller-dordrecht.nl
Telephone Bridge	+31 (0) 621 124 159
VSAT Telephone	+31 (0) 108 080 346

Muller Dordrecht

T +31 (0) 78 639 2000 (24/7) | E sales@muller-dordrecht.nl | muller-dordrecht.nl

in   

